
I-KONIC



MEALYN[®]
LVT FLOORING

A rich-toned palette that evokes timeless warmth



I-KONIC

Thickness : 1.5mm

Wear layer : 0.13mm

Size : 6' x 36'

Box packing : 32 pcs (48 sq.ft / 4.46 sq. mtr)



IK 1601



IK 1602



IK1603



IK1604

MECLYN®

I-KONIC

Thickness : 1.5mm

Wear layer : 0.13mm

Size : 6' x 36'

Box packing : 32 pcs (48 sq.ft / 4.46 sq. mtr)



IK 1605



IK 1606



IK1607



IK1608

MEALYN®

I-KONIC

Thickness : 1.5mm

Wear layer : 0.13mm

Size : 6' x 36'

Box packing : 32 pcs (48 sq.ft / 4.46 sq. mtr)



IK 1609



IK 1610



IK1611



IK1612

MEALYN®

I-KONIC

Thickness : 1.5mm

Wear layer : 0.13mm

Size : 6' x 36'

Box packing : 32 pcs (48 sq.ft / 4.46 sq. mtr)



IK 1613



IK 1614



IK1615



IK1616

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	RESULT
FIRE RATING	EN 13501-1	PASS
SLIP RESISTANCE	DIN 51130	R10
WEAR RESISTANCE	EN 660-2	≤ 2.0
WEAR GROUP	EN 649	T
DIMENSIONAL STABILITY	ISO 23999	≤0.15
RESIDUAL INDENTATION	ISO 24343	0.04
THERMAL CONDUCTIVITY	EN 14041	0.124
SOUND REDUCTION	DIN 52210	4 db
SQUARENESS	ISO 24342	≤ 0.05mm
COLOR FASTNESS	ISO 105-B02	6
FLEXIBILITY	ISO 24343-1	NO CRACKING

APPLICATIONS



HOSPITAL



RESIDENTIAL



SHOPPING MALLS



RETAIL



SCHOOL



HOTEL



OFFICES



LIBRARY

FEATURES



100 %
WATERPROOF



EASY TO
CLEAN



SOUND
ABSORBING



NATURAL
FEELING



HEALTH & SAFETY



NO BUGS&
TERMITES



PET
FRIENDLY



QUICK & EASY
INSTALLATION