
I-KONIC



MEALYN[®]
LVT FLOORING

A rich-toned palette that evokes timeless warmth

MECLYN[®]

I-KONIC

Thickness : 2mm

Wear layer : 0.2mm

Size : 6' x 36'

Box packing : 24 pcs (36 sq.ft / 3.34 sq. mtr)



IK 2501



IK 2502



IK 2503



IK 2504

MEALYN®

I-KONIC

Thickness : 2mm

Wear layer : 0.2mm

Size : 6' x 36'

Box packing : 24 pcs (36 sq.ft / 3.34 sq. mtr)



IK 2505



IK 2506



IK 2507



IK 2508

MEALYN®

I-KONIC

Thickness : 2mm

Wear layer : 0.2mm

Size : 6' x 36'

Box packing : 24 pcs (36 sq.ft / 3.34 sq. mtr)



IK 2509



IK 2510



IK 2511



IK 2512

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	RESULT
FIRE RATING	EN 13501-1	PASS
SLIP RESISTANCE	DIN 51130	R10
WEAR RESISTANCE	EN 660-2	≤ 2.0
WEAR GROUP	EN 649	T
DIMENSIONAL STABILITY	ISO 23999	≤0.15
RESIDUAL INDENTATION	ISO 24343	0.04
THERMAL CONDUCTIVITY	EN 14041	0.124
SOUND REDUCTION	DIN 52210	4 db
SQUARENESS	ISO 24342	≤ 0.05mm
COLOR FASTNESS	ISO 105-B02	6
FLEXIBILITY	ISO 24343-1	NO CRACKING

APPLICATIONS



HOSPITAL



RESIDENTIAL



SHOPPING MALLS



RETAIL



SCHOOL



HOTEL



OFFICES



LIBRARY

FEATURES



100 %
WATERPROOF



EASY TO
CLEAN



SOUND
ABSORBING



NATURAL
FEELING



HEALTH & SAFETY



NO BUGS&
TERMITES



PET
FRIENDLY



QUICK & EASY
INSTALLATION